



G-Tek™ MaxiFlex® Elite™
by ATG

MAXIMUM

SENSITIVITY, DEXTERITY & TACTILITY



MaxiFlex® Elite
G-Tek 34-244
9(L)
CE
EN 388
CAT 2
3121
Patent No. EP 1 808 808
www.atg-glovesolutions.com

36% & 30%
LIGHTER & THINNER
THAN TRADITIONAL FOAM NITRILE GLOVES



 FAMILY PRODUCT

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®
26 Computer Drive East | Albany, NY 12205 | 800-262-5755 | sales@pipusa.com | www.pipusa.com



UNPRECEDENTED STRENGTH-TO-WEIGHT RATIO IN HAND PROTECTION



G-Tek™ MaxiFlex® Elite™ by ATG

Designed and developed to be the lightest, fully breathable coated glove, the G-Tek™ MaxiFlex® Elite™ extends hand protection to new heights. Weighing 36% less and 30% thinner than traditional foam nitrile gloves, G-Tek™ MaxiFlex® Elite™ delivers a user experience that sets game-changing new standards.

360° breathability means they can be worn comfortably all day.

BASIC APPLICATIONS

Particularly advantageous on tasks where maximum sensitivity, dexterity and tactility is required, typically related to smaller parts or finer work such as:

- Fabrication
- Final Assembly
- Packaging**
- Finishing & Inspection
- Maintenance
- Logistics & Warehousing
- Wire Assembly (not live)
- Airport Security
- Food & Beverage Stores

ATG TECHNOLOGY MAKES IT HAPPEN

AIRtech® AirTech® Technology combines the advantages of thinner materials with breathability along with patented micro-foam nitrile coating. The result is an estimated 40% increase in breathability.

- ERGOtech®** ErgoTech® Technology
- 30% thinner foam nitrile gloves with comparable mechanical performance.
 - Ultra-light liner to produce smooth and rounded fingertips, maximizing fingertip sensitivity
 - ATG's superior design in form, fit and feel - mimics the "hand at rest", reducing hand fatigue and increasing comfort
 - Proven penetration free liner, long-lasting soft liner resting against the skin

PERFORMANCE PROPERTIES: EN388: 4121

| | | | | | | |
|----------|---|----------|----------|---|----------|---|
| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 |
| CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | |



SELECTING THE RIGHT GLOVE FOR THE JOB

- No dots best suited for dry applications, while dots on coating will significantly improve handling of wet pieces.
- ¾ dipped gloves will extend coating to just beyond the knuckle on the back side. This offers enhanced protection.

| ITEM # | COATING | FINISH | COLOR | LINER | SIZES | PALM THICKNESS | EN388 | SILICONE FREE |
|--------|----------|--------|-------|-------|----------|----------------|-------|---------------|
| 34-274 | Palm | n/a | Blue | Blue | XS - XXL | 0.75 mm | 4121 | Yes |
| 34-275 | ¾ dipped | n/a | Blue | Blue | XS - XL | 0.75 mm | 4121 | Yes |
| 34-244 | Palm | Dots | Blue | Blue | XS - XL | 0.75 mm | 4121 | No |
| 34-245 | ¾ dipped | Dots | Blue | Blue | XS - XL | 0.75 mm | 4121 | No |

