



TECHNICAL SHEET

09-K1600

G-TEK® KEV™ SEAMLESS KNIT KEVLAR® BLENDED GLOVE WITH NITRILE COATED FOAM GRIP ON PALM & FINGERS – 13 GAUGE, TOUCH SCREEN COMPATIBLE

- Seamless knit construction provides comfort without sacrificing dexterity
- Kevlar® fiber shell provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Touch screen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Launderable for extended life and to reduce replacement costs

APPLICATIONS

- Automotive
- Metal stamping
- Material handling
- Glass handling operations
- Fishing industries
- Sanitation
- General maintenance
- Waste handling
- Recycling

CARE INSTRUCTIONS

Machine wash in warm water with detergent. Rinse well and spin extract using high speed. Tumble dry on low to medium heat setting. Can be dry cleaned. Do not bleach.

TECHNICAL DATA

MATERIAL	Kevlar® / Nylon / Steel Fiber / Nitrile Coating				
CONSTRUCTION	Seamless knit				
COLOR	Shell: ■ Green/Black / Coating: ■ Black				
WRIST STYLE	Elastic knit				
SIZES	7 -11				
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case				
CASE DIMENSIONS	16.9" x 12.2" x 9.8" / 43cm x 31cm x 25cm				
CASE WEIGHT	7	8	9	10	11
	7.7 lbs 3.5 kgs	8.2 lbs 3.7 kgs	9.6 lbs 4.2 kgs	9.9 lbs 4.5 kgs	10.4 lbs 4.7 kgs
COO	China				

PERFORMANCE PROPERTIES

EN388: 4532	ASTM F2992-15 ANSI Cut Level A7 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-



DIMENSIONS (IN/CM)

	7	8	9	10	11
A	8.7 / 22	9.1 / 23.2	9.9 / 25.5	10.3 / 26.2	10.5 / 26.8
B	3.5 / 9	3.7 / 9.5	4.1 / 10.5	4.3 / 10.8	4.4 / 11.2
C	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

