



TECHNICAL SHEET

15-440

G-TEK® SUPRENE™ BLENDED GLOVE WITH NEOFOAM™ COATED GRIP



- Supreme™ fiber shell is 100 times stronger than steel and is amongst the highest performing fibers in cut and tear resistance
- Seamless knit construction provides comfort without sacrificing dexterity
- Neofoam™ coated palm and fingertips offers great abrasion resistance and outstanding wet/dry grip
- Touch screen compatible to allow the user to operate a touchscreen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Launderable for extended life and to reduce replacement costs
- Silicone free

APPLICATIONS

- Electronics
- General duty
- Parts assembly
- Construction

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).




TECHNICAL DATA

MATERIAL	Supreme™ Engineered Yarn / NeoFoam™ Coating					
CONSTRUCTION	Seamless knit					
COLOR	Shell: Tan/ Coating: Black					
WRIST STYLE	Knitted					
SIZES	6 -11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case					
CASE DIMENSIONS	15" x 11.8" x 10.6" / 38cm x 30cm x 27cm					
CASE WEIGHT	6	7	8	9	10	11
	7.5 lbs 3.4 kgs	8 lbs 3.7 kgss	8.8 lbs 4 kgs	10.4 lbs 4.7 kgs	11 lbs 4.9 kgs	11.3 lbs 5.2 kgs
COO	China					

DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	8.6 / 22	9 / 23	9.4 / 24	9.8 / 25	10.2 / 26	10.6 / 27
B	2.8 / 7.2	3.2 / 8.2	3.6 / 9.2	3.8 / 9.7	3.9 / 10	4.1 / 10.3
C	 Purple	 Red	 Yellow	 Brown	 Black	 Blue



PERFORMANCE PROPERTIES

EN388: 4542	ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-