



TECHNICAL SHEET

33-FG313/N



SEAMLESS KNIT POLYESTER GLOVE WITH POLYURETHANE COATED SMOOTH GRIP ON PALM & FINGERS

- Seamless knit nylon shell offers increased comfort, finger dexterity and breathability
- Polyurethane (PU) coatings offer great puncture and abrasion resistance while offering excellent tactile sensitivity
- Knit Wrist helps prevent dirt and debris from entering the glove
- Breathable back for comfort
- Pair packed for ease of distribution

APPLICATIONS

- Electronic and computer assembly
- Quality control
- Inspection
- General assembly
- Touch screen devices

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).



TECHNICAL DATA

| | |
|--------------|---|
| MATERIAL | Polyester with polyurethane coating on palm and fingers |
| CONSTRUCTION | Seamless knit |
| COLOR | Shell: ■ Black / Coating: ■ Black |
| WRIST STYLE | Continuous knit |
| SIZES | 6 -11 |
| PACKAGING | 1 pair per bag, 12 pairs per dozen, 120 pairs per case |
| COO | China |

DIMENSIONS (IN/CM)

| | 6 | 7 | 8 | 9 | 10 | 11 |
|---|------------|-----------|-----------|-----------|-----------|-----------|
| A | 8.5 / 21.5 | 9 / 23 | 9.4 / 24 | 9.8 / 28 | 10.2 / 26 | 10.6 / 27 |
| B | 3.5 / 9 | 3.6 / 9.2 | 3.7 / 9.5 | 3.8 / 9.8 | 4 / 10.2 | 4.3 / 11 |
| C | ■ Purple | ■ Red | ■ Yellow | ■ Brown | ■ Black | ■ Blue |

PERFORMANCE PROPERTIES

EN388: 4131

| | 0 | 1 | 2 | 3 | 4 | - |
|------------|---|---|---|---|---|---|
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT (2003) | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |

