



TECHNICAL SHEET

39-FG1315/RN



G-TEK® SEAMLESS KNIT NYLON GLOVE WITH LATEX COATED CRINKLE GRIP ON PALM & FINGERS

- Latex “Crinkle” coating provides superior grip in wet and dry conditions
- Knit Wrist helps prevent dirt and debris from entering the glove
- Seamless nylon knit shell is comfortable and flexible
- Ergonomic shaped curved finger pattern
- Breathable back for comfort

APPLICATIONS

- Assembly
- Construction
- Inspection
- Material handling
- Refuse handling
- Landscaping and gardening

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).



TECHNICAL DATA

MATERIAL	Nylon / Latex
CONSTRUCTION	Seamless knit
COLOR	Shell: ■ Red / Coating: ■ Gray
WRIST STYLE	Continuous knit
SIZES	7 -11
PACKAGING	1 pair per bag, 12 pairs per dozen, 120 pairs per case
COO	China

DIMENSIONS (IN/CM)

	7	8	9	10	11
A	9.2 / 23.5	9.4 / 24	10 / 25.5	10.2 / 26	11 / 28
B	3.5 / 9	3.8 / 9.7	3.9 / 10	4.1 / 10.5	4.3 / 11
C	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

PERFORMANCE PROPERTIES

EN388: 3131							
ABRASION	0	1	2	3	4	-	
CUT (2003)	0	1	2	3	4	5	
TEAR	0	1	2	3	4	-	
PUNCTURE	0	1	2	3	4	-	

