

# SPECIFICATION SHEET STYLE: 16-354



## **G-Tek® PolyKor®** Seamless Knit PolyKor® Blended Glove with Nitrile Coated Foam Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor<sup>™</sup> shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Nitrile is a synthetic rubber compound that offers excellent puncture, tear and abrasion resistance
- Foam Nitrile coatings are breathable and durable, designed with a cell structure that disperse fluids on contact for an improved grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

# Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- · Heavy to Medium Fastening and Anchoring



# **Technical Data**

| Color                | Black                          |
|----------------------|--------------------------------|
| Sizes Available      |                                |
| Packaging            | Bulk Pack                      |
| Packed               | 6/Case                         |
| Case Dimensions (cm) | 28.00 x 26.00 x 40.00          |
| Case Weight (kg)     | 5.54                           |
| Country of Origin    | China                          |
| Liner Material       | PolyKor                        |
| Coating              | Nitrile                        |
| Coating Color        | Black                          |
| Coating Coverage     | Palm & Fingers                 |
| Grip                 | Foam                           |
| Gauge                | 13                             |
| Cuff                 | Knit Wrist                     |
| Impact Protection    |                                |
| Construction         | Coated Seamless Knit, ESD Safe |
| Certifications       |                                |

## Performance Data

| EN 388                          | 4X43E |
|---------------------------------|-------|
| EN Abrasion Level               | 4     |
| EN Cut Level                    | Х     |
| EN Tear Level                   | 4     |
| EN Puncture Level               | 3     |
| EN TDM-100 Cut Level            | E     |
| ASTM F1358 Vertical Flame Level |       |
| EN 407                          |       |

## **Care Instructions**



Do Not Tumble Dry



#### PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU® AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-05-12