



### G-Tek® PolyKor® Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers - Touchscreen Compatible

- Seamless construction offers increased comfort and breathability
- Premium PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

### Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



4X43DX

### Technical Data

|                      |   |
|----------------------|---|
| Color                | Gray  |
| Sizes Available      | 8-10  |
| Packaging            | Pair Bagged Retail Ready                        |
| Packed               | 6 Dozen/Case                                    |
| Case Dimensions (cm) | 30.00 x 25.00 x 38.00                           |
| Case Weight (kg)     | 5.20  |
| Country of Origin    | China   |
| Liner Material       | PolyKor   |
| Coating              | Polyurethane                                    |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers                                  |
| Grip                 | Flat  |
| Gauge                | 13  |
| Cuff                 | Elastic   |
| Impact Protection    | --  |
| Construction         | Coated Seamless Knit,<br>Touchscreen Compatible |
| Certifications       | --  |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| EN 388                          | 4X43DX |
| EN Abrasion Level               | 4      |
| EN Cut Level                    | X      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 3      |
| EN TDM-100 Cut Level            | D      |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

### Care Instructions



Machine  
Wash



Water Temp  
40°C



Do Not  
Bleach



Tumble Dry



Low Heat