# 

## SPECIFICATION SHEET STYLE: 16-848-EN



#### G-Tek<sup>®</sup> PosiGrip MAX<sup>™</sup> 18 Gauge Seamless knit glove with HPPE/nylon/spandex blended liner, PosigripMax coating on palm & fingers - cut D.

- PosiGrip\* MAX Technology is a new, highly innovative coating designed to offer exceptional grip, durability, and comfort. Proprietary PosiGrip MAX<sup>™</sup> is a bi-polymer coating that has the best properties of both nitrile and polyurethane
- · PosiGrip® MAX gloves require up to 40% less force than traditional Nitrile (NBR) gloves for pulling and catching tasks,.
- PosiGrip® MAX<sup>™</sup> coating boasts near 0% oil penetration for safer skin and a reduced rate of glove changeouts from oil exposure
- 18 gauge for exceptional dexterity. ٠
- Integrated thumb reinforcement for longer life and added protection.
- The knitted cuff prevents dirt and debris from entering the glove. ٠



### **Technical Data**

| Color                | Purple                         |
|----------------------|--------------------------------|
| Sizes Available      | 6-11                           |
| Packaging            | Vend Packed                    |
| Packed               |                                |
| Case Dimensions (cm) |                                |
| Case Weight (kg)     | 0.00                           |
| Country of Origin    |                                |
| Liner Material       | HPPE, Nylon, Spandex           |
| Coating              | PosiGrip Max                   |
| Coating Color        | Black                          |
| Coating Coverage     | Palm & Fingers                 |
| Grip                 | MicroSurface                   |
| Gauge                | 18                             |
| Cuff                 | Knit Wrist                     |
| Impact Protection    |                                |
| Construction         | Coated Seamless Knit, Oil      |
|                      | Resistant, Reinforced Thumb    |
|                      | Crotch, Touchscreen Compatible |
| Certifications       | TAA Compliant                  |

#### Performance Data

| EN 388                          | 4X42D  |
|---------------------------------|--------|
| EN Abrasion Level               | 4      |
| EN Cut Level                    | х      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 2      |
| EN TDM-100 Cut Level            | D      |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          | X1XXXX |

 $\otimes$ 

Do Not Bleach

#### **Care Instructions**





Ο

Tumble Dry

Low Heat

#### PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-19