



### G-Tek® Paradox™

Seamless Knit PolyKor® Blended Glove with PosiGrip MAX™ Coating on Palm & Fingers with Reinforced Thumb Crotch - 21 Gauge - Touchscreen Compatible

- Seamless construction offers increased comfort and breathability
- Premium PolyKor® blended 21G shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Proprietary PosiGrip MAX™ is a bi-polymer coating that has the best properties of both nitrile and polyurethane
- This unique coating reduces required gripping force by up to 35% in dry/ oily conditions and provides enhanced tactility for handling small parts
- PosiGrip MAX™ coating boasts near 0% oil penetration for safer skin and a reduced rate of glove changeouts from oil exposure
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves



4X42F

### Technical Data

|                      |   |
|----------------------|---|
| Color                | --  |
| Sizes Available      | --  |
| Packaging            | Pair Bagged Plain   |
| Packed               | 12/Case   |
| Case Dimensions (cm) | 46.00 x 28.00 x 36.00   |
| Case Weight (kg)     | 8.66  |
| Country of Origin    | China   |
| Liner Material       | PolyKor   |
| Coating              | PosiGrip Max  |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers  |
| Grip                 | --  |
| Gauge                | 21  |
| Cuff                 | Knit Wrist  |
| Impact Protection    | --  |
| Construction         | Coated Seamless Knit, Reinforced Thumb Crotch, Touchscreen Compatible |
| Certifications       | Latex Free  |

### Performance Data

|                                 |       |
|---------------------------------|-------|
| EN 388                          | 4X42F |
| EN Abrasion Level               | 4     |
| EN Cut Level                    | X     |
| EN Tear Level                   | 4     |
| EN Puncture Level               | 2     |
| EN TDM-100 Cut Level            | F     |
| ASTM F1358 Vertical Flame Level | --    |
| EN 407                          | --    |