

# SPECIFICATION SHEET

STYLE: 19-D325



## G-Tek® 3GX®

Seamless Knit Dyneema® Diamond Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- · Seamless construction offers increased comfort and breathability
- Dyneema® Diamond & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

## **Applications**

- · Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- · Shipping, Receiving and Packaging



#### 4541C

### **Technical Data**

| Color                | White                      |
|----------------------|----------------------------|
| Sizes Available      |                            |
| Packaging            | Pair Bagged Retail Ready   |
| Packed               | 6/Case                     |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00      |
| Case Weight (kg)     | 5.20                       |
| Country of Origin    | China                      |
| Liner Material       | Dyneema Diamond Technology |
| Coating              | Polyurethane               |
| Coating Color        | White                      |
| Coating Coverage     | Palm & Fingers             |
| Grip                 | Flat                       |
| Gauge                | 13                         |
| Cuff                 | Knit Wrist                 |
| Impact Protection    |                            |
| Construction         | Coated Seamless Knit       |
| Certifications       |                            |

### **Performance Data**

| EN 388                          | 4541CX |
|---------------------------------|--------|
| EN Abrasion Level               | 4      |
| EN Cut Level                    | 5      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 1      |
| EN TDM-100 Cut Level            | С      |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |