

SPECIFICATION SHEET

STYLE: 19-D470



MaxiCut®

Seamless Knit Dyneema® / Engineered Yarn Glove with Nitrile Coated MicroFoam Grip on Palm & Fingers

- Nitrile MicroFoam coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- Innovative Fibers Unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- Reinforcement Between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area
- 360° Breathability Patented micro-foam nitrile coating offers 360° breathability making it the most breathable cut resistant glove on the market
- Form, Fit and Feel Mimics the "hand at rest", reducing hand fatigue and increasing comfort

Applications

- · Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- Handling, Assembly and Sorting
- · Finishing and Parts Inspection
- Industrial Applications
- Precision Construction Jobs



Technical Data

| Color | Gray |
|----------------------|--|
| Sizes Available | |
| Packaging | Bulk Pack |
| Packed | 6/Case |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00 |
| Case Weight (kg) | 4.90 |
| Country of Origin | Sri Lanka |
| Liner Material | Dyneema |
| Coating | Nitrile |
| Coating Color | Gray |
| Coating Coverage | Palm & Fingers |
| Grip | MicroFoam |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit, Reinforced Thumb Crotch |
| Certifications | 21 CFR, Silicone Free, Latex Free |

Performance Data

| EN 388 | 4443CX |
|---------------------------------|--------|
| EN Abrasion Level | 4 |
| EN Cut Level | 4 |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | С |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |