

SPECIFICATION SHEET STYLE: 250-95-0520



Technical Data

| Color | Black |
|----------------------|--|
| Sizes Available | OS |
| Packaging | |
| Packed | |
| Case Dimensions (cm) | |
| Case Weight (kg) | 0.00 |
| Country of Origin | Taiwan |
| Lens | Clear |
| Frame Style | Semi-Rimless |
| Lens Color | Clear |
| Frame Fit | Universal |
| Lens Coating | |
| Bridge | Molded |
| Temple | |
| Diopter | |
| Base Curve | 9.5 |
| Construction | |
| Certifications | TAA Compliant, EN 166, EN 170, EN 172 |

I-Tek

Safety-glasses with Polycarbonate lens. Frame : co-injected polycarbonate / Temples : co-injected polycarbonate + TPE Clear AS K/AF N FogLess[®] 3SIXTY[™]

- Pivoting and flexible bi-material temples provide the most comfortable non slip fit
- Soft adjustable anti-slip nose bridge offering optimal positioning
- The Soft flange co-injected directly all around the lens provides a full around fit and appropriate dust and particle protection from different sides
- This safety glass has no metal parts
- Available in Clear, Smoked, Clear KN and Indoor/Outdoor UV400 to give the right solution for every application

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-02-07