



# SPECIFICATION SHEET

## STYLE: 390-EZ150



### EZ-Cool® Evaporative Tank Top

- Can be worn over a breathable shirt, but designed to be worn against the skin
- Lightweight, athletic design that features a nylon/spandex outer shell and inner HyperKewl™ cooling fabric with water repellent liner
- 1-2 minute activation time
- Can provide 5-10 hours of cooling relief per activation
- Cools the body 15-20 degrees from the ambient temperature
- Provides uniform cooling effect without the swelling and slime effect
- Dries after use and when stored properly eliminates the chance of mold or mildew
- Side zip closure for easy on/off
- Built-in ventilation on sides and back
- Always store in clean, dry conditions that are not in direct, strong sunlight
- Machine washable

### Technical Data

|                      |                       |
|----------------------|-----------------------|
| Color                | Black                 |
| Sizes Available      | --                    |
| Packaging            | Bagged Each           |
| Packed               | 25/Case               |
| Case Dimensions (cm) | 40.60 x 40.60 x 40.60 |
| Case Weight (kg)     | 11.30                 |
| Country of Origin    | China                 |
| Fabric               | Nylon, HyperKewl      |
| Closure              | Zipper                |
| Construction         | --                    |
| Certifications       | --                    |

### Performance Data

|                 |             |
|-----------------|-------------|
| Activation Time | 1-2 Minutes |
|-----------------|-------------|

### Care Instructions



Machine  
Wash



Water Temp  
60°C



Do Not  
Bleach



Tumble Dry



Medium Heat

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-05-12