

SPECIFICATION SHEET

STYLE: 44-3445



MaxiCut® Ultra DT™

Seamless Knit Engineered Yarn Glove with Premium Nitrile Coated MicroFoam Grip on Palm & Fingers - Micro Dot Palm

- Innovative fibres ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort.
- Reinforcement between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area.
- 360° breathability patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market today.
- Form, fit and feel mimics the "hand at rest", reducing hand fatigue and increasing comfort.
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Latest knitting technology utilized to produce smooth and rounded fingertips, improving fingertip sensitivity

Applications

- Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- Handling, Assembly and Sorting
- · Finishing and Parts Inspection
- Industrial Applications
- Precision Construction Jobs





45420

Technical Data

| Color | Blue |
|----------------------|---|
| Sizes Available | |
| Packaging | Bulk Pack |
| Packed | 6/Case |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00 |
| Case Weight (kg) | 5.35 |
| Country of Origin | Sri Lanka |
| Liner Material | Engineered Yarn |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | MicroFoam |
| Gauge | 15 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit, Reinforced Thumb Crotch, Touchscreen Compatible |
| Certifications | 21 CFR, Latex Free |

Performance Data

| EN 388 | 4542CX |
|---------------------------------|--------|
| EN Abrasion Level | 4 |
| EN Cut Level | 5 |
| EN Tear Level | 4 |
| EN Puncture Level | 2 |
| EN TDM-100 Cut Level | С |
| ASTM F1358 Vertical Flame Level | |
| FN 407 | |