



Technical Data

Color	--
Sizes Available	39-48
Packaging	--
Packed	--
Case Dimensions (cm)	--
Case Weight (kg)	0.00
Country of Origin	China
Material	Textile
Outsole	--
Toe Type	--
Tread Pattern	--
Height	--
Construction	--
Certifications	--

Performance Data

ASTM F2413 Requirement	--
------------------------	----

PUMA® Safety

Rush 2.0 MID S1P ESD HRO SRC Composite Toe Electrostatic Dissipative Shoes, Heat Resistant, Slip Resistant, Safety Shoes

- **RUBBER OUTSOLE MOTION** - The 572°F heat resistant HRO rubber sole is inspired by the latest running technology. The anti-slip sole profile with its diagonal grooves ensures perfect flexibility and secure contact to the ground (SRC). A nylon shank is integrated in the sole concept.
- **FLEX GROOVES** - The diagonal grooves in the sole profile provide a better flexibility and a smoother feel on the ground. Furthermore, they will give you a better grip while walking.
- **TORSION CONTROL ELEMENT** - The TPU torsion control element in the middle of the sole supports the natural flexing action of the foot while walking and provides a better support and stability for the feet.
- **IMPULSE FOAM MIDSOLE** - The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. Thereby the IMPULSE.FOAM® does not only return up to 55% of the energy, but also provides maximum cushioning, excellent stability and long-lasting comfort.
- **EVERCUSHION® BA** - This anatomically designed footbed provides a high level of comfort and moisture control, giving a pleasant foot climate. This footbed, as used in high performance sports shoes, is made from a soft, open-cell, resilient foam that will not compress in wear, which ensures a high level of cushioning, breathability and moisture regulation.