

SPECIFICATION SHEET

STYLE: 643700



Technical Data

Color	stone
Sizes Available	39-48
Packaging	
Packed	
Case Dimensions (cm)	
Case Weight (kg)	0.00
Country of Origin	China
Material	Microfiber
Outsole	
Toe Type	Composite
Tread Pattern	
Height	
Construction	
Certifications	

Performance Data

ASTM F2413 Requirement --

PUMA® Safety

Vanti Grey LOW Composite Toe Electrostatic Dissipative Shoes, Fuil Oil resistant, Heat Resistant, Slip Resistant, Safety Boots

- RUBBER OUTSOLE MOTION The 572°F heat resistant HRO rubber sole is inspired by the latest running technology. The anti-slip sole profile with its diagonal grooves ensures perfect flexibility and secure contact to the ground (SRC). A nylon shank is integrated in the sole concept.
- FLEX GROOVES The diagonal grooves in the sole profile provide a better flexibility and a smoother feel on the ground. Furthermore, they will give you a better grip while walking.
- TORSION CONTROL ELEMENT The TPU torsion control element in the middle of the sole supports the natural flexing action of the foot while walking and provides a better support and stability for the feet.
- IMPULSE FOAM MIDSOLE The innovative IMPULSE.FOAM®
 midsole in two different densities reacts to each of your steps with
 an energy impulse. Thereby the IMPULSE.FOAM® does not only
 return up to 55% of the energy, but also provides maximum
 cushioning, excellent stability and long-lasting comfort.
- EVERCUSHION® BA This anatomically designed footbed provides a high level of comfort and moisture control, giving a pleasant foot climate. This footbed, as used in high performance sports shoes, is made from a soft, open-cell, resilient foam that will not compress in wear, which ensures a high level of cushioning, breathability and moisture regulation.