

SPECIFICATION SHEET

STYLE: 643860



Packaging - Packed - Case Dimensions (cm) - Case Weight (kg) 0.00 Country of Origin China Material Textile

grey/blue 39-48

Performance Data

ASTM F2413 Requirement

Technical Data

Color

Outsole
Toe Type
Tread Pattern
Height
Construction
Certifications

Sizes Available

PUMA® Safety

Xcite Grey LOW S1P ESD HRO SRC Composite Toe Electrostatic Dissipative Shoes, Heat Resistant, Slip Resistant, Safety Boots

- RUBBER OUTSOLE MOTION The 572°F heat resistant HRO rubber sole is inspired by the latest running technology. The anti-slip sole profile with its diagonal grooves ensures perfect flexibility and secure contact to the ground (SRC). A nylon shank is integrated in the sole concept.
- FLEX GROOVES The diagonal grooves in the sole profile provide a better flexibility and a smoother feel on the ground. Furthermore, they will give you a better grip while walking.
- TORSION CONTROL ELEMENT The TPU torsion control element in the middle of the sole supports the natural flexing action of the foot while walking and provides a better support and stability for the feet.
- IMPULSE FOAM MIDSOLE The innovative IMPULSE.FOAM®
 midsole in two different densities reacts to each of your steps with
 an energy impulse. Thereby the IMPULSE.FOAM® does not only
 return up to 55% of the energy, but also provides maximum
 cushioning, excellent stability and long-lasting comfort.
- EVERCUSHION® BA This anatomically designed footbed provides a high level of comfort and moisture control, giving a pleasant foot climate. This footbed, as used in high performance sports shoes, is made from a soft, open-cell, resilient foam that will not compress in wear, which ensures a high level of cushioning, breathability and moisture regulation.

ASTWITZ413 Hequirement

Care Instructions



Hand Wash

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®