

SPECIFICATION SHEET STYLE: 646200-210

Color Sizes Available

Technical Data



Performance Data

ASTM F2413 Requirement -



Albatros®

Ultratrail Black LOW S3 ESD HRO SRC Composite Toe Electrostatic Dissipative Shoes, Heat Resistant, Slip Resistant, Safety Boots

- SLIP RESISTANT XTS TRAIL OUTSOLE The easy-to-clean rubber outsole ensures perfect contact with the ground. It is non-slip and abrasion-proof and heat-resistant up to 300°C (HRO). The specially designed cleat profile and the wide flex grooves guarantee optimal flexion, optimize the water-displacing properties (windshield wiper effect) and provide a secure hold on a wide variety of surfaces.
- IMPULSE.FOAM® midsole Ultimate comfort during long working days. The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. Thereby the IMPULSE.FOAM® does not only return the energy, but also provides maximum cushioning and excellent stability.
- FAP FLEXIBLE ANTI-PENETRATION FAP® is a non-metallic material, especially for safety footwear, made of multiple textile layers of extremely tearproof fibers. The FAP® midsole offers greater comfort, flexibility, cold insulation, humidity absorption and shock absorption to the wearer.
- FIBERGLASS TOE CAP Fiberglass reinforced composite toe cap with more space for the toes, lighter than a common steel cap, antimagnetic and thermally insulating.
- comfit® AIR FOOTBED The newly developed, breathable
 ALBATROS® comfit® AIR footbed has elevations in the heel and ball
 area of the foot as well as a support of the longitudinal arch. This
 helps the foot keeping its natural position in the shoe and stimulates
 the musculature while walking. The slip-resistant textile cover is
 odour-resistant, moisture absorbing and washable at 30°C.