



Technical Data

Color	schwarz-blau
Sizes Available	36-47
Packaging	--
Packed	--
Case Dimensions (cm)	--
Case Weight (kg)	0.00
Country of Origin	China
Material	Textile
Outsole	--
Toe Type	--
Tread Pattern	--
Height	--
Construction	--
Certifications	--

Performance Data

ASTM F2413 Requirement	--
------------------------	----

Albatros®

Breeze Impulse QI LOW S1P ESD HRO SRA
Composite Toe Electrostatic Dissipative Shoes,
Heat Resistant, Slip Resistant, Safety Boots

- **DUAL IMPULSE SLIP RESISTANT OUTSOLE** - The easy to clean rubber outsole ensures perfect ground contact. It is non-slip and abrasion resistant as well as heat resistant up to 300°C (HRO). The specially designed cleat profile and the wide flex grooves guarantee optimum flexion, optimize the water-displacing properties (windscreen wiper effect) and provide firm grip on a wide variety of grounds.
- **IMPULSE.FOAM® midsole** - Ultimate comfort during long working days. The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. Thereby the IMPULSE.FOAM® does not only return the energy, but also provides maximum cushioning and excellent stability.
- **comfit® AIR FOOTBED** - The newly developed, breathable ALBATROS® comfit® AIR footbed has elevations in the heel and ball area of the foot as well as a support of the longitudinal arch. This helps the foot keeping its natural position in the shoe and stimulates the musculature while walking. The slip-resistant textile cover is odour-resistant, moisture absorbing and washable at 30°C.
- **FAP® - Flexible Anti Perforation** - The flexible anti-perforation midsole made of ceramic-coated fibers, reliably protects the feet completely from penetrating objects.

Care Instructions



Hand Wash