



2542C

Technical Data

Color	Yellow
Sizes Available	--
Packaging	Pair Bagged Retail Ready
Packed	6/Case
Case Dimensions (cm)	65.00 x 27.00 x 22.00
Case Weight (kg)	6.10
Country of Origin	China
Liner Material	Aramid
Coating	--
Coating Color	Black
Coating Coverage	--
Grip	Smooth
Gauge	--
Palm	--
Back	--
Cuff	Knit Wrist
Impact Protection	--
Construction	Coated Seamless Knit
Certifications	--

Maximum Safety®

AR/FR Seamless Knit Aramid Glove with Nitrile Coated Smooth Grip on Palm & Fingers

- Arc Rating: ATPV 7.4 cal/cm2 (ASTM F2675 / ASTM F2675M)
- PPE 1 (HRC 1)
- Seamless construction offers increased comfort and breathability
- Aramid fiber liner adds heat resistance, cut resistance and strength
- Foam Nitrile coated palm and fingers are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove

Applications

- Installation, Maintenance, and Repairing Electrical Distribution and Transmission System
- Framing and Setting Poles and Meters
- Attaching and Testing Grounding Devices to Remove Electrical Hazards

Performance Data

PPE Category	1
EN 388	2542CX
EN Abrasion Level	2
EN Cut Level	5
EN Tear Level	4
EN Puncture Level	2