

SPECIFICATION SHEET STYLE: CCNQH2-26NV



Uniform Technology™ Spray Barrier Paint / Powder Coating Hooded Coverall

- Spray Barrier Fabric 99% Polyester / 1% Carbon
- Raglan sleeves for more movement
- · Mesh vented back with flap, mesh vented underarms
- Coil zipper
- · Elastic at sleeve hems
- One inside breast pocket
- Two patch hip pockets with flaps
- Waist tabs with snaps on back
- · Hemmed legs with snap adjustments
- · Side seam pockets
- Hood elastic around face with snap closure
- Horizontal and vertical snaps on back of hood



Technical Data

Color	Navy
Sizes Available	
Packaging	Case
Packed	1/Case
Case Dimensions (cm)	61.00 x 40.60 x 30.50
Case Weight (kg)	1.13
Country of Origin	Mexico
Clothing Type	Coveralls
Fabric	Spray Barrier
Closure	Zipper
Construction	ESD Safe
Certifications	TAA Compliant

Performance Data

ISO Cleanroom	
ANSI/ESD S20.20	
Temperature Resistant	
Static Control Property	

Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.