



### Kut Gard®

#### Seamless Knit ATA® / Aramid Blended Glove with Cotton/Polyester Plating - Heavy Weight

- ATA® Technology blend is exceptionally comfortable, offers twice the cut resistance compared with traditional Para-Aramid gloves and is inherently flame resistant
- Cotton/Polyester plating maximizes comfort
- Knit Wrist helps prevent dirt and debris from entering the glove
- Launderable for extended life and to reduce replacement costs
- Made in the USA
- ASTM F1060-08 Level 3 Contact heat, 3rd party tested

### Applications

- Cut Resistance with Light Heat Protection
- Automotive Applications
- Glass Operations

### Technical Data

|                      |                                      |
|----------------------|--------------------------------------|
| Color                | Yellow                               |
| Sizes Available      | --                                   |
| Packaging            | Bulk Pack                            |
| Packed               | 6/Case                               |
| Case Dimensions (cm) | 50.80 x 35.56 x 27.94                |
| Case Weight (kg)     | 8.35                                 |
| Country of Origin    | United States                        |
| Liner Material       | Aramid, Cotton, Stainless Steel Wire |
| Coating              | Uncoated                             |
| Gauge                | 7                                    |
| Cuff                 | Knit Wrist                           |
| Hide                 | --                                   |
| Impact Protection    | --                                   |
| Construction         | Machine Knit, Seamless Knit          |
| Certifications       | TAA Compliant                        |

### Performance Data

|                                 |    |
|---------------------------------|----|
| EN 388                          | -- |
| EN Abrasion Level               | -- |
| EN Cut Level                    | -- |
| EN Tear Level                   | -- |
| EN Puncture Level               | -- |
| EN TDM-100 Cut Level            | -- |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407                          | -- |

### Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat