

# SPECIFICATION SHEET

STYLE: 44-505



## MaxiCut® Oil

Seamless Knit Engineered Yarn Glove with Nitrile Coated MicroFoam Grip on Palm, Fingers & Knuckles

- Micro-Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- Reinforcement between the thumb and forefinger
- Patented micro-foam nitrile coating offers 360° breathability making it the most breathable cut resistant glove on the market
- The Skin Health Alliance has awarded professional dermatological accreditation following review of the scientific dossier behind this product
- Silicone Free

### **Applications**

- Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- · Handling, Assembly and Sorting
- Finishing and Parts Inspection
- Industrial Applications
- Precision Construction Jobs



#### **Technical Data**

| Color                | Blue   |
|----------------------|--|
| Sizes Available      |  |
| Packaging            | Bulk Pack  |
| Packed               | 6/Case   |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00                            |
| Case Weight (kg)     | 8.20   |
| Country of Origin    | Sri Lanka  |
| Liner Material       | Engineered Yarn                                  |
| Coating              | Nitrile  |
| Coating Color        | Black  |
| Coating Coverage     | Palm, Fingers & Knuckles                         |
| Grip                 | MicroFoam  |
| Gauge                | 15   |
| Cuff                 | Knit Wrist                                       |
| Impact Protection    |  |
| Construction         | Coated Seamless Knit,<br>Reinforced Thumb Crotch |
| Certifications       | Silicone Free, Latex Free                        |

#### **Performance Data**

| EN 388                          | 4442CX |
|---------------------------------|--------|
| EN Abrasion Level               | 4      |
| EN Cut Level                    | 4      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 2      |
| EN TDM-100 Cut Level            | С      |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |