



G-Tek® KEV™

Seamless Knit DuPont™ Kevlar® Glove with Double-Dipped Nitrile Coated MicroSurface Grip on Palm & Fingers - Vend-Ready

- Vend pack ready for Personal Protective Equipment (PPE) vending machines in the industrial workplace
- Seamless knit construction provides comfort without sacrificing dexterity
- Kevlar® fiber shell provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Double-Dipped Nitrile MicroSurface coatings are impermeable providing an elevated grip in dry and oily conditions, infused with thousands of tiny suction cup pockets that create a vacuum effect that dispenses fluids away on contact
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



4343X

Technical Data

| | |
|----------------------|-----------------------|
| Color | Yellow |
| Sizes Available | -- |
| Packaging | Vend Packed |
| Packed | 72/Case |
| Case Dimensions (cm) | 56.00 x 22.00 x 24.00 |
| Case Weight (kg) | 6.30 |
| Country of Origin | China |
| Liner Material | Kevlar |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | MicroSurface |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit |
| Certifications | -- |

Performance Data

| | |
|---------------------------------|-------|
| EN 388 | 4343X |
| EN Abrasion Level | 4 |
| EN Cut Level | 3 |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | -- |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |

Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat