



### G-Tek® VR-X™

Seamless Knit PolyKor® Blended Glove with Polyurethane Advanced Barrier Coating Protection – Touchscreen Compatible

- Seamless construction offers increased comfort and breathability
- VR-X Polyurethane coatings provide advanced barrier protection, the treated coating takes on the surface properties of the glove liner providing a tactile grip in wet, dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Liquid proof, air leak tested - EN374-2
- Antibacterial and antiviral barrier protection per ISO 20743:2013 test method & EN374-5
- 4.0 AQL, similar to the AQL levels for industrial grade disposable gloves
- ESD Safe, Surface Resistance per ESD S11.1 Static dissipative range at 10<sup>9</sup> ohms, 12%RH, 48hrs @100Volts

### Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



### Technical Data

Color	Black
Sizes Available	6-11
Packaging	Pair Bagged Retail Ready
Packed	6 Dozen/Case
Case Dimensions (cm)	38.00 x 31.00 x 27.00
Case Weight (kg)	5.00
Country of Origin	China
Liner Material	HPPE
Coating	Polyurethane
Coating Color	Black
Coating Coverage	Full Hand
Grip	Foam
Gauge	18
Cuff	Knit Wrist
Impact Protection	--
Construction	Coated Seamless Knit, Touchscreen Compatible
Certifications	Silicone Free, ANSI/ESD S11.11

### Performance Data

EN 388	4X32CX
EN Abrasion Level	4
EN Cut Level	X
EN Tear Level	3
EN Puncture Level	2
EN TDM-100 Cut Level	C
ASTM F1358 Vertical Flame Level	--
EN 407	--

### Care Instructions

