



SPECIFICATION SHEET

STYLE: HSCBM1P-48NV



Uniform Technology™

Microdenier ESD Sitewear Bottom

- ESD Microdenier Fabric - 99% Polyester / 1% Carbon
- 1" elastic waist
- Elastic and snap adjustment at leg seams
- Color coded loop



Technical Data

Color	Navy
Sizes Available	--
Packaging	Case
Packed	1/Case
Case Dimensions (cm)	61.00 x 40.60 x 30.50
Case Weight (kg)	0.91
Country of Origin	China
Clothing Type	Sitewear
Fabric	ESD Microdenier
Closure	Elastic
Construction	ESD Safe
Certifications	--

Performance Data

ISO Cleanroom	--
ANSI/ESD S20.20	--
Temperature Resistant	--
Static Control Property	Static Dissipative

Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-10