ESD

## Technical Data

| | |
|---|---|
| Color | Royal |
| Sizes Available | -- |
| Packaging | Case |
| Packed | 1/Case |
| Case Dimensions (cm) | 61.00 x 40.60 x 30.50 |
| Case Weight (kg) | 27.01 |
| Country of Origin | China |
| Clothing Type | Coveralls |
| Fabric | Auto Grid |
| Closure | Zipper & Snap |
| Construction | ESD Safe, Low-Lint |
| Certifications | -- |

## Performance Data

| | |
|---|---|
| ISO Cleanroom | -- |
| ANSI/ESD S20.20 | -- |
| Temperature Resistant | -- |
| Static Control Property | Static Dissipative |

## Uniform Technology™
Auto Grid Cleanroom Paint/Powder Coating Coverall

- Auto Grid - 99% Polyester 1% Carbon
- Overlap collar with snaps
- Raglan sleeves for more movement
- Rubber button and buttonholes on back sleeve hem
- Patch pockets at left front breast and right hip
- White tricot vents at upper back, side back and leg inseam

## Care Instructions

Our garments do not come wearer ready meaning they need to be laundered before an employee wears them in an ISO class cleanroom. Average wear and tear lifespan is 50-100 washes. Make sure all zippers and snaps are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (140°F). After drying tumble dry cold for 5 minutes. No iron.