

SPECIFICATION SHEET

STYLE: 09-K1320



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Latex Coated Crinkle Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell with Aramid PolyKor® is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance while providing protection in heat resistant applications, where sparks and heat are present
- Latex "Crinkle" coated palm and fingertips provides superior grip in wet/dry conditions and offers abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Launderable for extended life and to reduce replacement costs

Applications

- Secure Wet or Dry Grip, Tear and Puncture Resistant
- Handling and Cleanup of Heavy to Medium Abrasive Parts and Materials
- Demolition
- Masonry and Tile
- Steel Rod and Metal Fastening and Assembly



Technical Data

| Color | Yellow |
|----------------------|-----------------------|
| Sizes Available | |
| Packaging | Bulk Pack |
| Packed | 6/Case |
| Case Dimensions (cm) | 32.00 x 30.00 x 50.00 |
| Case Weight (kg) | 7.30 |
| Country of Origin | China |
| Liner Material | PolyKor |
| Coating | Latex |
| Coating Color | Blue |
| Coating Coverage | Palm & Fingers |
| Grip | Crinkle |
| Gauge | 10 |
| Cuff | Elastic |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | |

Performance Data

| EN 388 | 3X43CX |
|---------------------------------|--------|
| EN Abrasion Level | 3 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | С |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions









