

SPECIFICATION SHEET

STYLE: 44-5745E



MaxiCut® Ultra™

Seamless Knit Engineered Yarn with Premium Nitrile Coated MicroFoam Grip on Palm & Fingers - Touchscreen Compatible

- Innovative fibers ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- 360° breathability patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market
- Reinforcement Between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area
- Consistent liner penetration from the nitrile, leaving only the soft liner resting against the skin
- Form, fit and feel mimics the "hand at rest", reducing hand fatigue and increasing comfort
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves



Technical Data

| Color | Dark Gray |
|----------------------|--|
| Sizes Available | |
| Packaging | Bulk Pack |
| Packed | 6/Case |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00 |
| Case Weight (kg) | 4.20 |
| Country of Origin | Sri Lanka |
| Liner Material | Polyester, Spandex, Stainless Steel Wire |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | MicroFoam |
| Gauge | 15 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Reinforced Thumb Crotch, Seamless Knit, Touchscreen Compatible |
| Certifications | Silicone Free, Latex Free |

Performance Data

| EN 388 | 4343E |
|---------------------------------|-------|
| EN Abrasion Level | 4 |
| EN Cut Level | 3 |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | E |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions

40°C











