



### MaxiCut® Ultra™

Seamless Knit Engineered Yarn with Premium Nitrile Coated MicroFoam Grip on Palm & Fingers - Touchscreen

- Innovative fibers - ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- 360° breathability - patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market today
- Reinforcement - Between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area
- Consistent liner penetration - from the nitrile, leaving only the soft liner resting against the skin
- Form, fit and feel - mimics the "hand at rest", reducing hand fatigue and increasing comfort
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves



4243F

### Technical Data

|                      |   |
|----------------------|---|
| Color                | Black   |
| Sizes Available      | --  |
| Packaging            | Bulk Pack   |
| Packed               | --  |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00   |
| Case Weight (kg)     | 4.34  |
| Country of Origin    | Sri Lanka   |
| Liner Material       | Nylon, Polyester, UHMWPE, Spandex                                     |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm & Fingers  |
| Grip                 | MicroFoam   |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    | --  |
| Construction         | Coated Seamless Knit, Touchscreen Compatible, Reinforced Thumb Crotch |
| Certifications       | Silicone Free, EU Food Approved, Latex Free                           |

### Performance Data

|                                 |       |
|---------------------------------|-------|
| EN 388                          | 4243F |
| EN Abrasion Level               | 4     |
| EN Cut Level                    | 2     |
| EN Tear Level                   | 4     |
| EN Puncture Level               | 3     |
| EN TDM-100 Cut Level            | F     |
| ASTM F1358 Vertical Flame Level | --    |
| EN 407                          | --    |

### Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat