



### G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Double-Dipped Latex Coated MicroSurface Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Double-Dipped Latex MicroSurface coatings are impermeable providing an elevated grip in dry and oily conditions, infused with thousands of tiny suction cup pockets that create a vacuum effect that dispenses fluids away on contact
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

### Applications

- Secure Wet or Dry Grip, Tear and Puncture Resistant
- Handling and Cleanup of Heavy to Medium Abrasive Parts and Materials
- Demolition
- Masonry and Tile
- Steel Rod and Metal Fastening and Assembly



3543CX

### Technical Data

|                      |                          |
|----------------------|--------------------------|
| Color                | Salt & Pepper            |
| Sizes Available      | --                       |
| Packaging            | Pair Bagged Retail Ready |
| Packed               | 6/Case                   |
| Case Dimensions (cm) | 57.00 x 31.00 x 22.00    |
| Case Weight (kg)     | 5.90                     |
| Country of Origin    | China                    |
| Liner Material       | PolyKor                  |
| Coating              | Latex                    |
| Coating Color        | Black                    |
| Coating Coverage     | Palm & Fingers           |
| Grip                 | MicroSurface             |
| Gauge                | 13                       |
| Cuff                 | Knit Wrist               |
| Impact Protection    | --                       |
| Construction         | Coated Seamless Knit     |
| Certifications       | --                       |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| EN 388                          | 3543CX |
| EN Abrasion Level               | 3      |
| EN Cut Level                    | 5      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 3      |
| EN TDM-100 Cut Level            | C      |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

### Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat