



G-Tek® ECO Series™

Seamless Knit Dyneema® Diamond 2.0 Blended Glove with Latex Coated Crinkle Grip on Palm & Fingers - Medium Weight

- Seamless construction offers increased comfort and breathability
- Dyneema® Diamond 2.0 & Spandex shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Dyneema® bio-based fibers equates to 450g of CO2 emissions reduction per pair when compared to traditional Dyneema® fibers
- Latex crinkle coatings feature creases or wrinkles on the surface of the coating that are designed to channel fluids away allowing better contact on dry or wet surfaces – a natural rubber that is flexible, tough and durable due to its high degree of resistance to snagging, puncture, and abrasion
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

Applications

- Secure Wet or Dry Grip, Tear and Puncture Resistant
- Handling and Cleanup of Heavy to Medium Abrasive Parts and Materials
- Demolition
- Masonry and Tile
- Steel Rod and Metal Fastening and Assembly



4X43D

Technical Data

| | |
|----------------------|--------------------------------|
| Color | White |
| Sizes Available | -- |
| Packaging | Pair Bagged Retail Ready |
| Packed | -- |
| Case Dimensions (cm) | 30.00 x 32.00 x 42.00 |
| Case Weight (kg) | 7.20 |
| Country of Origin | Viet Nam |
| Liner Material | Dyneema Diamond 2.0 Technology |
| Coating | Latex |
| Coating Color | Blue |
| Coating Coverage | Palm & Fingers |
| Grip | Crinkle |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit |
| Certifications | 21 CFR |

Performance Data

| | |
|---------------------------------|-------|
| EN 388 | 4X43D |
| EN Abrasion Level | 4 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | D |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |