



### MaxiCut® Ultra DT™

Seamless Knit Engineered Yarn Glove with Premium Nitrile Coated MicroFoam Grip on Palm, Fingers & Knuckles - Micro Dot Palm

- Innovative fibres - ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort.
- Reinforcement - between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area.
- 360° breathability - patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market today.
- Form, fit and feel - mimics the "hand at rest", reducing hand fatigue and increasing comfort.
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Latest knitting technology - utilized to produce smooth and rounded fingertips, improving fingertip sensitivity.

### Applications

- Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- Handling, Assembly and Sorting
- Finishing and Parts Inspection
- Industrial Applications
- Precision Construction Jobs



4542CX

### Technical Data

|                      |   |
|----------------------|---|
| Color                | Blue  |
| Sizes Available      | 6-11  |
| Packaging            | Bulk Pack   |
| Packed               | 6 Dozen/Case  |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00   |
| Case Weight (kg)     | 5.25  |
| Country of Origin    | Sri Lanka   |
| Liner Material       | Engineered Yarn   |
| Coating              | Nitrile   |
| Coating Color        | Black   |
| Coating Coverage     | Palm, Fingers & Knuckles  |
| Grip                 | Dot   |
| Gauge                | 15  |
| Cuff                 | Knit Wrist  |
| Impact Protection    | --  |
| Construction         | Coated Seamless Knit, Reinforced Thumb Crotch, Touchscreen Compatible |
| Certifications       | 21 CFR, Latex Free  |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| EN 388                          | 4542CX |
| EN Abrasion Level               | 4      |
| EN Cut Level                    | 5      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 2      |
| EN TDM-100 Cut Level            | C      |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |