



Technical Data

| | |
|----------------------|---|
| Color | Blue |
| Sizes Available | -- |
| Packaging | Vend Packed |
| Packed | 72/Case |
| Case Dimensions (cm) | 50.00 x 29.50 x 20.00 |
| Case Weight (kg) | 4.85 |
| Country of Origin | Sri Lanka |
| Liner Material | Engineered Yarn |
| Coating | Nitrile |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | MicroFoam |
| Gauge | 15 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit, Reinforced Thumb Crotch, Touchscreen Compatible |
| Certifications | 21 CFR, Silicone Free, Latex Free |

MaxiCut® Ultra™

Seamless Knit Engineered Yarn Glove with Premium Nitrile Coated MicroFoam Grip on Palm & Fingers - Touchscreen Compatible - Vend-Ready

- Vend pack ready for Personal Protective Equipment (PPE) vending machines in the industrial workplace
- Innovative fibres - ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- Reinforcement - between the thumb and forefinger, improves cut resistance and extends glove life in an inherently weak area
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- 360° breathability - patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market today
- Form, fit and feel - mimics the "hand at rest", reducing hand fatigue and increasing comfort

Applications

- Good Grip, Durable Coating, Premium Performance
- Mechanical Equipment Maintenance and Repair
- Handling, Assembly and Sorting
- Finishing and Parts Inspection
- Industrial Applications
- Precision Construction Jobs

Performance Data

| | |
|---------------------------------|--------|
| EN 388 | 4442CX |
| EN Abrasion Level | 4 |
| EN Cut Level | 4 |
| EN Tear Level | 4 |
| EN Puncture Level | 2 |
| EN TDM-100 Cut Level | C |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |