



### G-Tek® 3GX® Black

Seamless Knit Dyneema® Diamond Blended Glove with Nitrile Coated Foam Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- Dyneema® shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Foam Nitrile coatings are breathable and durable, designed with a cell structure that disperse fluids on contact for an improved grip
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Black coloring hides the dirt better than lighter colored gloves
- Knit Wrist helps prevent dirt and debris from entering the glove

### Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



4543CX

### Technical Data

|                      |                            |
|----------------------|----------------------------|
| Color                | Black                      |
| Sizes Available      | --                         |
| Packaging            | Pair Bagged Retail Ready   |
| Packed               | 6/Case                     |
| Case Dimensions (cm) | 30.00 x 32.00 x 36.00      |
| Case Weight (kg)     | 6.30                       |
| Country of Origin    | China                      |
| Liner Material       | Dyneema Diamond Technology |
| Coating              | Nitrile                    |
| Coating Color        | Black                      |
| Coating Coverage     | Palm & Fingers             |
| Grip                 | Foam                       |
| Gauge                | 13                         |
| Cuff                 | Knit Wrist                 |
| Impact Protection    | --                         |
| Construction         | Seamless Knit              |
| Certifications       | --                         |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| EN 388                          | 4543CX |
| EN Abrasion Level               | 4      |
| EN Cut Level                    | 5      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 3      |
| EN TDM-100 Cut Level            | C      |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

### Care Instructions



Machine Wash



Water Temp 40°C



Do Not Bleach



Tumble Dry



Low Heat

**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobalsafety.com](http://www.pipglobalsafety.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-05