



G-Tek® PolyKor® Xrystal® Seamless Knit PolyKor® Xrystal® Blended Glove with NeoFoam® Coated Palm & Fingers - Touchscreen Compatible

- Seamless construction offers increased comfort and breathability
- PolyKor® Xrystal® shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- NeoFoam® offers an incredibly secure grip in dry conditions, a versatile and flexible coating that provides breathability and a high degree of dexterity, ideal for handling and the assembly of parts
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification

Applications

- Secure Dry and Flexible Grip
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging
- Maintenance and Repair Operations



4X42EX

Technical Data

| | |
|----------------------|---|
| Color | Black |
| Sizes Available | -- |
| Packaging | Pair Bagged Retail Ready |
| Packed | -- |
| Case Dimensions (cm) | 38.00 x 31.00 x 29.00 |
| Case Weight (kg) | 5.70 |
| Country of Origin | China |
| Liner Material | PolyKor Xrystal |
| Coating | Neofoam |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | Foam |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit, Touchscreen Compatible |
| Certifications | 21 CFR, Silicone Free |

Performance Data

| | |
|---------------------------------|--------|
| EN 388 | 4X42EX |
| EN Abrasion Level | 4 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 2 |
| EN TDM-100 Cut Level | E |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | -- |