

# SPECIFICATION SHEET

STYLE: 16-319



# G-Tek® PolyKor®

18 Gauge Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers - Cut B

- · Seamless construction offers increased comfort and breathability
- PolyKor® shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips provides a secure grip in dry and slightly wet/oily conditions and offers high dexterity and tactile sensitivity
- · Knit wrist helps prevent dirt and debris from entering the glove
- · Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

## **Applications**

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



#### **Technical Data**

| Color                | Blue  |
|----------------------|---|
| Sizes Available      | 6-11  |
| Packaging            |   |
| Packed               | 6 Dozen/Case                                    |
| Case Dimensions (cm) |   |
| Case Weight (kg)     | 0.00  |
| Country of Origin    | China   |
| Liner Material       | PolyKor   |
| Coating              | Polyurethane                                    |
| Coating Color        | Blue  |
| Coating Coverage     | Palm & Fingers                                  |
| Grip                 | Flat  |
| Gauge                | 18  |
| Cuff                 | Knit Wrist                                      |
| Impact Protection    |   |
| Construction         | Coated Seamless Knit,<br>Touchscreen Compatible |
| Certifications       |   |

### **Performance Data**

| EN 388                          | 3X41BX |
|---------------------------------|--------|
| EN Abrasion Level               | 3      |
| EN Cut Level                    | X      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 1      |
| EN TDM-100 Cut Level            | В      |
| ASTM F1358 Vertical Flame Level |        |
| EN 407                          |        |

### **Care Instructions**









