

SPECIFICATION SHEET

STYLE: 713DGU



Barracuda®

Seamless Knit Polykor Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- Polykor blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging



Technical Data

| Color | Gray |
|----------------------|-----------------------|
| Sizes Available | |
| Packaging | Bulk Pack |
| Packed | 10/Case |
| Case Dimensions (cm) | 49.53 x 30.48 x 29.21 |
| Case Weight (kg) | 25.85 |
| Country of Origin | Viet Nam |
| Liner Material | PolyKor |
| Coating | Polyurethane |
| Coating Color | Gray |
| Coating Coverage | Palm & Fingers |
| Grip | Flat |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | |
| Construction | Coated Seamless Knit |
| Certifications | |

Performance Data

| EN 388 | 4X42DX |
|---------------------------------|--------|
| EN Abrasion Level | 4 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 2 |
| EN TDM-100 Cut Level | D |
| ASTM F1358 Vertical Flame Level | |
| EN 407 | |

Care Instructions











 \odot