



### Kut Gard®

#### Seamless Knit DuPont™ Kevlar® Glove with Double-Sided PVC Dot Grip - Half-Finger

- Dupont Kevlar® fiber construction provides high tensile strength relative to its weight, is inherently cut resistant and will not melt, ignite or conduct electricity
- Seamless knit construction protects hands without sacrificing comfort or dexterity
- Double-sided PVC dots provide enhanced grip and extra cut and abrasion resistance
- Half-finger for greater dexterity, sensitivity and breathability
- Color coded hems for easy size identification
- Custom styles and modifications available

### Applications

- Cut Resistance with Light Heat Protection
- Automotive Applications
- Glass Operations

### Technical Data

|                      |                            |
|----------------------|----------------------------|
| Color                | Yellow                     |
| Sizes Available      | --                         |
| Packaging            | Bulk Pack                  |
| Packed               | --                         |
| Case Dimensions (cm) | 30.48 x 30.48 x 30.48      |
| Case Weight (kg)     | 3.86                       |
| Country of Origin    | United States              |
| Liner Material       | Kevlar                     |
| Coating              | PVC                        |
| Coating Color        | Blue                       |
| Grip                 | Dot                        |
| Gauge                | 7                          |
| Cuff                 | Knit Wrist                 |
| Impact Protection    | --                         |
| Construction         | Seamless Knit, Half Finger |
| Certifications       | TAA Compliant              |

### Performance Data

|                                 |    |
|---------------------------------|----|
| EN 388                          | B  |
| EN Abrasion Level               | -- |
| EN Cut Level                    | -- |
| EN Tear Level                   | -- |
| EN Puncture Level               | -- |
| EN TDM-100 Cut Level            | B  |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407                          | -- |