



### G-Tek® PosiGrip® Seamless Knit PolyKor® Blended Glove with Nitrile Coated Smooth Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Nitrile smooth/flat coatings are highly impermeable to liquids, proving a very tacky dry grip for specific applications that require secure holding power
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

### Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring



4543CX

### Technical Data

|                      |                       |
|----------------------|-----------------------|
| Color                | Gray                  |
| Sizes Available      | --                    |
| Packaging            | Bulk Pack             |
| Packed               | --                    |
| Case Dimensions (cm) | 39.69 x 30.48 x 29.53 |
| Case Weight (kg)     | 4.99                  |
| Country of Origin    | China                 |
| Liner Material       | PolyKor               |
| Coating              | Nitrile               |
| Coating Color        | Black                 |
| Coating Coverage     | Palm & Fingers        |
| Grip                 | Smooth                |
| Gauge                | 13                    |
| Cuff                 | Knit Wrist            |
| Impact Protection    | --                    |
| Construction         | Coated Seamless Knit  |
| Certifications       | --                    |

### Performance Data

|                                 |        |
|---------------------------------|--------|
| EN 388                          | 4543CX |
| EN Abrasion Level               | 4      |
| EN Cut Level                    | 5      |
| EN Tear Level                   | 4      |
| EN Puncture Level               | 3      |
| EN TDM-100 Cut Level            | C      |
| ASTM F1358 Vertical Flame Level | --     |
| EN 407                          | --     |

### Care Instructions



Machine  
Wash



Water Temp  
40°C



Do Not  
Bleach



Tumble Dry



Low Heat