



G-Tek® Typhan™

G-Tek Typhan® XLT1 - 13 Gauge Seamless cut resistant knit glove with XREY™ blended liner and premium crinkle latex coating on palm & fingers.
- Cut F.

- Seamless construction offers increased comfort and breathability
- The Patented XREY™ yarn has one of the highest strength to weight ratio and allows it to remove the need for any glass or steel within the liner, removing the chance of any irritation for the wearer. Our X-REY™ fiber is 15X stronger than HPPE at the same weight. Fine and soft, it is 25% lighter than other fibers. •NO STEEL • NO GLASS FIBER • NO TUNGSTEN • NO BASALT
- The premium blue crinkle latex coating is excellent for use in wet or dry environments, coupling enhanced grip with excellent abrasion resistance.
- 13 Gauge.
- Knit Wrist helps prevent dirt and debris from entering the glove.
- Washable for extended life and reduced replacement costs.



Technical Data

| | |
|----------------------|---------------------------------------|
| Color | Gray |
| Sizes Available | 6-11 |
| Packaging | Bulk Pack |
| Packed | -- |
| Case Dimensions (cm) | -- |
| Case Weight (kg) | 0.00 |
| Country of Origin | -- |
| Liner Material | Engineered Yarn |
| Coating | Latex |
| Coating Color | Blue |
| Coating Coverage | Palm & Fingers |
| Grip | Crinkle |
| Gauge | 13 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit, Water Resistant |
| Certifications | TAA Compliant |

Performance Data

| | |
|---------------------------------|--------|
| EN 388 | 3X43F |
| EN Abrasion Level | 3 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 3 |
| EN TDM-100 Cut Level | F |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | X1XXXX |

Care Instructions



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-06-13