



G-Tek® PosiGrip MAX™

18 Gauge Seamless knit glove with HPPE/nylon/spandex blended liner, PosigripMax coating on palm & fingers - cut B.

- PosiGrip® MAX Technology is a new, highly innovative coating designed to offer exceptional grip, durability, and comfort. Proprietary PosiGrip MAX™ is a bi-polymer coating that has the best properties of both nitrile and polyurethane
- PosiGrip® MAX gloves require up to 40% less force than traditional Nitrile (NBR) gloves for pulling and catching tasks.
- PosiGrip® MAX™ coating boasts near 0% oil penetration for safer skin and a reduced rate of glove changeouts from oil exposure
- 18 gauge for exceptional dexterity.
- Up to 30% lighter than standard gloves, ideal for prolonged use.
- Integrated thumb reinforcement for longer life and added protection.



Technical Data

| | |
|----------------------|--------------------------------------------------------------------------------------|
| Color | Purple |
| Sizes Available | 6-11 |
| Packaging | Vend Packed |
| Packed | -- |
| Case Dimensions (cm) | -- |
| Case Weight (kg) | 0.00 |
| Country of Origin | -- |
| Liner Material | HPPE, Nylon, Spandex |
| Coating | PosiGrip Max |
| Coating Color | Black |
| Coating Coverage | Palm & Fingers |
| Grip | MicroSurface |
| Gauge | 18 |
| Cuff | Knit Wrist |
| Impact Protection | -- |
| Construction | Coated Seamless Knit, Oil Resistant, Reinforced Thumb Crotch, Touchscreen Compatible |
| Certifications | TAA Compliant |

Performance Data

| | |
|---------------------------------|--------|
| EN 388 | 4X42B |
| EN Abrasion Level | 4 |
| EN Cut Level | X |
| EN Tear Level | 4 |
| EN Puncture Level | 2 |
| EN TDM-100 Cut Level | B |
| ASTM F1358 Vertical Flame Level | -- |
| EN 407 | X1XXXX |

Care Instructions

