



Technical Data

Color	Gray/Pink
Sizes Available	35-42
Packaging	
Packed	
Case Dimensions (cm)	
Case Weight (kg)	0.00
Country of Origin	Viet Nam
Material	
Outsole	
Тое Туре	
Tread Pattern	
Height	
Construction	
Certifications	

Performance Data

ASTM F2413 Requirement

PUMA® Safety CELERITY KNIT PINK LOW S1PS ESD FO HRO SR

- MOTION WNS SOLE Heat resistant up to 300°C, the tread on the rubber outsole delivers perfect contact on a wide variety of surfaces. The lateral elevation of the midsole in the heel area, which is frequently used in running, improves the stability of heel contact.
- TRIPLE ARCH SUPPORT SYSTEM The perfectly balanced arch supports of outsole, evercushion* EASY foobed and ergonomic last create a harmonious unit and deliver optimized foot support.
- FAP* LITE FLEXIBLE ANTI-PERFORATION The latest generation of metal-free antiperforation: • 50% lighter* • excellent flexibility • improved cushioning and pressure elasticity • breathability and sweat absorption for a cooling effect
- EVERCUSHION® EASY The combination of breathable, open-cell foam technology and particularly moistureabsorbing upper material effectively transports perspiration away from the feet and keeps them pleasantly dry. The soft memory foam of the evercushion® EASY footbed adapts perfectly to the shape of the foot and exhibits truly outstanding cushioning effects – for the softest of touches with every step.

PROTECTIVE INDUSTRIAL PRODUCTS, INC. BRINGING THE BEST OF THE WORLD TO YOU*

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2025-07-03